


PRODUCT TYPE	TRADE TERM	QUOTATION
SYSTEM	CPU	HC1703
	Nor Flash	16MB
	SDRAM	64MB DDR2 (Built-in CPU)
	Image Sensor	SC223A
	System	Linux
CAMERA CONFIG	Image Sensor Config.	2MP 1/2.8" CMOS
	Shutter	Auto
	Lens	4mm @F2.2
	Field of View (FOV)	Horizontal 85° , Vertical 45° , Diagonal 102°
	PTZ Angle	Horizontal 356° , Vertical 60°
	Lens Mount	M12
	Day & Night	Automatic IR cut filter
	Noise Reduction (DNR)	3D Noise Reduction
IMAGE	Dynamic Range	WDR
	Resolution	1920 × 1080 pixel
COMPRESSION	Frame	25 FPS
	Video Compression	H.265
WiFi	Video Compression Rate	FHD, HD, SD
	WiFi Standards	IEEE802.11b, 802.11g, 802.11n Draft
	Frequency Range	2.4 GHz - 2.4835 GHz
	Channel Bandwidth	Support 20MHz , 40MHz
	Safety	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
INTERFACES	Speed	11b: 11Mbps, 11g :54Mbps, 11n :150Mbps
	DC	*1/ Micro USB 5V 1A Power Supply
	Reset	*1
	MIC	*1
	Speaker	*1
	Photodiode	*1
FEATURES	TF Card Slot	*1
	2.4G Antenna	*1
	Storage	Support MicroSD /Max 128G Support Cloud Storage Support Alarm Record
	Night Vision	up to 8m in distance
	Talkback	Two-way audio
	OTA Upgrade	Supported
	Pairing	Scan QR code
	STAVIX App for monitoring	Supported
	Motion Detection	Supported
	Regional Alarm	Supported
	Human Figure Detection	Supported
	Human Figure Tracking	Supported
OTHERS	Sound Detection	Supported
	ONVIF	Supported
	Preset Position	Support 11 Preset Positions
	Operating Condition	Temperature: -10 °C to +50 °C Humidity: < 95%
	Power Supply	Micro USB 5V 1A
	Power Consumption	≤ 5W
	Size	122*70*70mm
	Weight	185 g (excluding package)
		

产品规格

产品外观