

IUFUTURE PRODUCT

4CH PoE NVR

SPECIFICATION

SYSTEM	CPU	MC6810
	Nor Flash	16MByte SPI Flash
VIDEO INPUT	DDR	2Gbit DDR3
	Operation System	Linux
	IP Camera Inputs	Max 4 Channels
	Main Code Stream	5MP/4MP/3MP/2MP
	Sub Code Stream	D1/VGA/640×360/CIF
VIDEO OUTPUT	Video Input Bandwidth	64Mbps
	Video Output Bandwidth	64Mbps
RECORDING	Output Type	HDMI/VGA
	Resolution	4-ch@2MP, 1-ch@5MP
HDD (optional)	Resolution	5MP/4MP/3MP/2MP
	Recording Mode	Timer, Motion Detection, Smart
	Synchronous playback channels	1ch@5MP/4MP/3MP 2ch@2MP/1.3MP/1MP
	Search Mode	Channel, Time/Date, Event Type
	Playback Function	Play, Pause, Stop, Rewind, Fast Play, Slow Play, Full Screen
	Backup Mode Compatibility	USB Device; Network
INTERFACES	Port Type	*1 SATA port
	Capacity	Up to 8TB HDD (3.5 inch)
	Storage Management	Record Plan Configuration Hard Disk Format, Hard Disk Status
FEATURES	HDMI	*1
	VGA	*1
	WAN	*1/ RJ45,10/100M self-adaption
	LAN/POE	*4/RJ45,10/100M, Supported POE Standard
	DC IN	*1
	USB	USB 2.0 *2
OTHERS	IPC Access Mode	Automatic Search, Custom Add, One-click Add
	IPC Remote Management	IP Address Setting, Image Parameter Setting, Event Parameter Setting
	Alert Type	Motion Detection, Video Loss Alarm, Humanoid Detection Sound Detection, Device Abnormality Alarm
	Auto Recording	Supported
	HDMI/VGA Simultaneous Output	Supported
	App for monitoring	Supported
	PC client monitoring	iCMS
	ONVIF	Supported
	GB28181	Supported
	OTA Upgrade	Supported
	POE Standard	IEEE 802.3af/at
	POE Mode	Normal Mode, Enhanced Mode (POE distance up to 200 meters)
	Buzzer	Supported
	Indicator Light	Network Indicator, Hard Disk Indicator, Power Indicator
Operating Temperature	-10℃~+50℃	
Working Humidity	10%~90%	
Power	DC 48V 1A external adaptor	
Consumption (excl. HDD)	MAX 48W	
Dimensions	235*225*44 mm	
Weight	605g (without HDD)	

PICTURES

