

PRODUCT SPECIFICATION

PRODUCT TYPE	TRADE TERM	QUOTATION	
SPECIFICATION	SYSTEM	CPU	GK7605V100
		Nor Flash	16MB
		SDRAM	128MB DDR3
		Image Sensor	GC4653
		OS	Linux
	CAMERA CONFIG	Image Sensor Config.	4MP 1/3" CMOS
		Shutter	Auto
		Lens	4mm @F2.0
		Field of View (FOV)	Horizontal 76°, Vertical 42°, Diagonal 89°
		Lens Mount	M12
		Day & Night	Automatic IR cut filter
		Noise Reduction (DNR)	3D Noise Reduction
		Dynamic Range	WDR
	IMAGE	Resolution	2560 × 1440 pixel
		Frame	30 FPS
	COMPRESSION	Video Compression	H.265
		H.265 Encoding	H.265 Main Profile
		Video Compression Rate	FHD, HD, SD
	FEATURES	STAVIX App for monitoring	Supported
		Tuya App for monitoring	Supported
		Mic	Supported
		Fill Light Distance	IR: 15m White Light: 15m
		Storage	Support Cloud Storage
		Motion Detection	Supported
		Human Body Detection	Supported
		Sound Detection	Supported
		ONVIF	Supported
		Waterproof	IP66
OTA Upgrade		Supported	
INTERFACES	DC	*1/ 12V Power Supply	
	Reset	*1	
	LAN/PoE	*1/ RJ45,10/100M self-adaption POE Standard,IEEE 802.3af,44V-57V INPUT(Optional)	
OTHERS	Operating Condition	Temperature: -10 °C to +50 °C Humidity:< 95%	
	Power Supply	DC 12V±5% 1A	
	Power Consumption	Max 12W	
	Size	109.4*109.4*95.5mm	
	Weight	275g (excluding package)	
PICTURES			