

PRODUCT IUFUTURE

PRODUCT TYPE		TRADE TERM	QUOTATION	
产品外观	CAMERA CONFIG	Image Sensor Config.	2MP 1/2.9" CMOS	
		Shutter	Auto	
		Lens	3.2mm @F2.6	
		Field of View (FOV)	Horizontal 109° , Diagonal 136° , Vertical 58°	
		Lens Mount	M12	
		Day & Night	Automatic IR cut filter	
		Noise Reduction (DNR)	3D Noise Reduction	
		Dynamic Range	WDR	
	IMAGE	Resolution	1920 × 1080 pixel	
		Frame	20 FPS	
	COMPRESSION	Video Compression	H.265	
		H.265 Encoding	H.265 main profile@level5.1 Main Tier	
		Video Compression Rate	FHD	
	WIFI	WiFi Standards	IEEE802.11b, 802.11g, 802.11n Draft	
		Frequency Range	2.412 GHz - 2.472 GHz	
		Channel Bandwidth	Supports 20MHz , 40MHz	
		Safety	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK	
		Speed	11b: 11Mbps, 11g :54Mbps, 11n :150Mbps	
	INTERFACES	Type-C	*1/ DC 5V 1A Power Supply	
		Battery Compartments	*1/ Lithium battery Power Supply (5200mAH)	
		Doorbell button	*1	
		Power Switch	*1	
		Reset	*1	
		MIC	*1	
		Speaker	*1	
		TF Card Slot	*1	
		Indicator Light	*1/ R/B two color LED indicator light	
		Photosensitive Diode	*1	
		PIR	*1	
		2.4G Antenna	*1/ Built-in 2.4G Antenna	
		433M Antenna	*1/ Built-in 433M Antenna	
	FEATURES	Storage	Support MicroSD /Max 128G Support Alarm Record Storage	
		Indoor machine	Supported	
		PIR	up to 6m in distance (Sensitivity High / Medium / Low adjustable)	
		Face Detection	Supported	
		Human Figure Detection	Supported	
		Night Vision	up to 7m in distance	
		Talkback	Two-way audio	
		OTA Upgrade	Supported	
		Pairing	Scan QR code	
		Call Alert	Supported	
		Low-power Alert	Supported	
		STAVIX App for monitoring	Supported	
		Tuya Smart App for monitoring	Supported	
		Activate ways	Press the doorbell , PIR Motion detected , Tamper Alarm, App	
		Tamper Alarm	Supported	
		Doorbell Ringtone	Ringtone optional , volume adjustable	
		Waterproof	IP65	
		AC Power Supply	Supported	
		USB Power Supply	Supported	
		OTHERS	Operating Condition	Temperature: -10 °C to +50 °C Humidity:< 95%
			Power Supply	DC 5V 1A /18650 Battery/AC 8-24V
			Indoor machine Power	AC 100V-240V
			Doorbell Power Consumption	≤ 1W
	Size		140*51*36mm	
	Weight		220g (excluding package)	
	Installation		3M adhesive tape, screws fixed to the wall	
				